

S 180 C HT

FEP/SIR 가동용 제어 차폐 케이블 (번호식별/고온용)



Construction:

Conductor:	tinned copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
Insulation:	FEP
Colour code:	black cores with consecutive numbers acc. to EN 50334; green-yellow earth wire from 3 cores
Stranding:	specially adjusted layering with non-woven tape over each layer
Wrapping:	tape
Screen:	tinned copper braiding
Sheath material:	special Besilen®
Sheath colour:	grey (similar RAL 7000)

Outstanding features:

- very good EMC characteristics
- extreme temperature resistance
- high notch resistance
- very good flexibility
- EAC approval

Technical data:

Nominal voltage:	U ₀ /U 0,6/1 kV
Testing voltage U:	4000 V acc. to EN 50264
Min. bending radius continuously flexible:	15 x d
Temperature range	
fixed laying:	-25/+180 °C
flexible application:	-25/+180 °C
short-time use:	+200 °C
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + EN 60332-1-2
Flexibility:	very good
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
31850315	3 x 1,50	0,15	8,1	63,8	110
31850415	4 x 1,50	0,15	8,9	80,4	137
31850515	5 x 1,50	0,15	9,6	98,3	166
31850715	7 x 1,50	0,15	11,4	147,6	240
31850325	3 x 2,50	0,15	9,8	98,5	163
31850425	4 x 2,50	0,15	11,1	142,1	221
31850525	5 x 2,50	0,15	12,1	171,9	268
31850725	7 x 2,50	0,15	14,0	229,2	364
31850440	4 x 4,00	0,15	12,7	206,4	304
31850540	5 x 4,00	0,15	14,0	253,2	378
31850740	7 x 4,00	0,15	16,7	368,0	541
31850460	4 x 6,00	0,20	15,2	297,9	457
31850560	5 x 6,00	0,20	17,2	388,0	568
31850760	7 x 6,00	0,20	20,2	519,5	780
31850461	4 x 10,0	0,20	17,8	485,6	683
31850561	5 x 10,0	0,20	19,7	594,9	828
31850462	4 x 16,0	0,20	21,5	747,7	1007
31850562	5 x 16,0	0,20	24,0	922,4	1256
31850463	4 x 25,0	0,20	25,2	1117,5	1444
31850464	4 x 35,0	0,20	29,0	1532,5	1934

Other dimensions and colours are possible on request.



Application:
for use
in cable tracks
with extremely
ambient temperature
like for example
in steel industry!