


# SL 820

TPE/PUR 모터 연결 케이블



Marking for SL 820 C 08200415:

SAB BRÖCKSKES · D-VIERSEN · SL 820 0,6/1 kV 4 x 1,5 mm² C€

## Construction:

<b>Conductor:</b>	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
<b>Insulation:</b>	TPE
<b>Colour code:</b>	black cores with consecutive numbers acc. to EN 50334 and a green-yellow earth wire
<b>Stranding:</b>	in layers
<b>Wrapping:</b>	non-woven tape
<b>Sheath material:</b>	PUR, TPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
<b>Sheath colour:</b>	orange (RAL 2003)

## Outstanding features:

- very high flexibility
- suitable for cable tracks
- oil resistant
- very long service life
- adhesion-free installation
- halogen-free
- labs uncritical  
(labs = enamel moistening interfering substances)
- flexible at low temperatures
- EAC approval

## Technical data:

<b>Nominal voltage:</b>	U <sub>0</sub> /U 0.6/1 kV
<b>Testing voltage U:</b>	4000 V
<b>Min. bending radius</b>	
fixed laying:	4 x d
flexible application:	6 x d
continuously flexible:	10 x d
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg
<b>Temperature range</b>	
fixed laying:	-50/+90 °C
flexible application:	-40/+90 °C
<b>Oil resistance:</b>	very good - TPU acc. to DIN VDE 0282 part 10 + HD 22.10
<b>Chem. resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.
<b>Weather resistance:</b>	very good
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page N/17



for DNC motors  
on frequency  
converters

item no.	no. of cores x cross section n x mm <sup>2</sup>	AWG	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
08200415	4 x 1,50	16 / 4c	0,16	8,5	57,6	102
08200515	5 x 1,50	16 / 5c	0,16	9,3	72,0	125
08200425	4 x 2,50	14 / 4c	0,16	10,7	96,0	160
08200525	5 x 2,50	14 / 5c	0,16	11,4	120,0	193
08200440	4 x 4,00	12 / 4c	0,16	12,4	153,6	247
08200540	5 x 4,00	12 / 5c	0,16	13,2	192,0	290
08200460	4 x 6,00	10 / 4c	0,21	15,1	230,4	351
08200560	5 x 6,00	10 / 5c	0,21	16,5	288,0	443
08200470	4 x 10,0	8 / 4c	0,21	17,5	384,0	552
08200570	5 x 10,0	8 / 5c	0,21	19,2	480,0	641
08200480	4 x 16,0	6 / 4c	0,21	21,2	614,4	796
08200580	5 x 16,0	6 / 5c	0,21	23,3	768,0	979
08200490	4 x 25,0	4 / 4c	0,21	24,3	960,0	1161
08200590	5 x 25,0	4 / 5c	0,21	26,8	1200,0	1433
08200495	4 x 35,0	2 / 4c	0,21	28,6	1344,0	1588
08200496	4 x 50,0	1 / 4c	0,31	32,3	1920,0	2212

Other dimensions and colours are possible on request.